



PLAN

LEGEND:

	CARRIAGEWAY
	FOOTPATH
	KERBLINE

TACTILE BLISTER PAVING, RED FINISH (400x400mm)

NOTES:

1. A CLEAR FOOTPATH PASSAGE WIDTH OF 1.2m SHOULD BE MAINTAINED BETWEEN ALL STREET FURNITURE, TREES ETC.
2. FOR CONSTRUCTION DETAIL REFER TO CC-SCD-05133, FOR TACTILE PAVING, RECOMMENDED GRADIENTS AND TRAFFIC SIGNAL POLE DETAILS REFER TO CC-SCD-05135, CC-SCD-05137 & CC-SCD-05139.
3. FOR DETAILS OF THE LENGTH OF ZIGZAG MARKINGS REFER TO THE TRAFFIC SIGNS MANUAL.
4. THIS LAYOUT CAN ALSO BE USED FOR A TOUCAN CROSSING BUT WITH A CROSSING WALKWAY WIDTH OF 4m TO 5m.
5. DROPPED KERBS MUST BE LAID FLUSH WITH CARRIAGEWAY SURFACE, WITH AN ABSOLUTE MAXIMUM UPSTAND OF 6mm.
6. FOR SIGNAL BOX PLACEMENT REFER TO SECTION 5.4.3.3 OF DN\_GEO\_03084.

ACTIVITY	PUBLICATION TITLE	HISTORICAL REFERENCE			DOCUMENTATION SET		PUBLICATION DATE	PUBLICATION NUMBER
		STREAM	STANDARD CONSTRUCTION DETAIL (SCD)	N/A	STANDARD			
							JULY 2021	CC SCD 05127